

**Safety Data Sheet**

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

JMC Silikonentferner

UFI: S02X-TXYG-DG0Q-RAHH

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reactive cleaning/removal agent

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Johannes J. Matthies GmbH & Co. KG

Street: Hammerbrookstr. 97

Place: D-20097 Hamburg

Telephone: + 49 (0) 40 2 37 21-0

Telefax: + 49 (0) 40 2 37 21-363

E-mail: info@matthies.de

Internet: www.matthies.de

Responsible Department: Abteilung Produktsicherheit

Supplier

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

Place: GB-NN17 5DP Corby

Telephone: + 44 1536 265633

E-mail: info@larsson.uk.com

Internet: www.larsson.uk.com

1.4. Emergency telephone number:

+ 44 1536 265633

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229

Asp. Tox. 1; H304

Skin Irrit. 2; H315

Eye Irrit. 2; H319

STOT SE 3; H336

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

propan-2-ol; isopropyl alcohol; isopropanol

acetone; propan-2-one; propanone

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane

Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 2 of 14

Pictograms:**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
 The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 3 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			25 - < 50 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
67-64-1	acetone; propan-2-one; propanone			20 - < 25 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane			10 - < 15 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics			5 - < 10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
124-38-9	Carbon Dioxide			3 - < 5 %
	204-696-9			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	25 - < 50 %
	inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5280 mg/kg		
67-64-1	200-662-2	acetone; propan-2-one; propanone	20 - < 25 %
	inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg		
	921-024-6	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane	10 - < 15 %
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg		
64742-49-0	927-510-4	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics	5 - < 10 %
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = 5500 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice.

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 4 of 14

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause drowsiness or dizziness.

Headache, Nausea, Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water mist. Foam, Carbon dioxide (CO₂), Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

Wear personal protection equipment (refer to section 8).

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 5 of 14

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Personal protection equipment: see section 8
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe in addition any national regulations!

Hints on joint storage

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances, Food and feedingstuffs

Further information on storage conditions

Protect against: Frost. Protect against direct sunlight. Store in a cool dry place. Observe in addition any national regulations!

7.3. Specific end use(s)

Reactive cleaning/removal agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Whole blood (B)

Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Tightly sealed safety glasses. (DIN EN 166)

Hand protection

Protect skin by using skin protective cream.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber).

Breakthrough time: 480 min

Thickness of the glove material: 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Respiratory protection necessary at: exceeding exposure limit values

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 7 of 14

Suitable respiratory protection apparatus: gas filtering equipment (EN 141).

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe in addition any national regulations!

Environmental exposure controls

Avoid release to the environment.

Observe in addition any national regulations!

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic
Odour threshold:	not determined

Test method

pH-Value (at 20 °C):	not determined	DIN 19268
----------------------	----------------	-----------

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	56 °C
Flash point:	- 26 °C

Flammability

Solid/liquid:	Flammable aerosol.
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	14,3 vol. %
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,76 g/cm ³ DIN 51757
Water solubility:	practically insoluble

Solubility in other solvents

not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic:	not determined
Relative vapour density:	not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 8 of 14

mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 5280 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2000 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat	Manufacturer	
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	Manufacturer	
	dermal	LD50 20000 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat	Manufacturer	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane				
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Manufacturer	
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Manufacturer	OECD 403

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 9 of 14

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol; acetone; propan-2-one; propanone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas (fathead minnow) Daphnia magna (Big water flea)	Manufacturer
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Manufacturer
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna (Big water flea)	Manufacturer
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	Manufacturer
	Acute algae toxicity	ErC50 mg/l	5000	96 h	Desmodesmus subspicatus	Manufacturer
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	Manufacturer
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane					
	Acute fish toxicity	LC50 mg/l	> 1 - 10	96 h	Pimephales promelas (fathead minnow)	Manufacturer
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Manufacturer OECD 201
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna	Manufacturer
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics					
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer (Study report(1995)) OECD 201
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	Manufacturer SIDS IARF SIAM
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	Manufacturer
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer SIDS IARF SIAM

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301B	90,9 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane			
	OECD 301F	98 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 11 of 14

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
67-64-1	acetone; propan-2-one; propanone	-0,24
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane	3,4 - 5,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 12 of 14

Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Marine pollutant: -
Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: See SP277
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 13 of 14

14.6. Special precautions for user

Warning: Flammable gases

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions:	No information available.
---	---------------------------

Directive 2004/42/EC on VOC in paints and varnishes:	No information available.
--	---------------------------

Information according to Directive 2012/18/EU (SEVESO III):	P3b FLAMMABLE AEROSOLS
---	------------------------

Additional information

Regulation (EC) No. 648/2004 (Detergents regulation)

Aerosol directive (75/324/EEC)

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
--------------------------	--

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

EU: European Union

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

REACH: Registration, Evaluation and Authorization of Chemicals

UN: United Nations

PBT: Persistent, Bioaccumulative, Toxic

SVHC: Substance of Very High Concern

vPvB: very Persistent, very Bioaccumulative

ATE: Acute Toxicity Estimates

BCF: Bio-Concentration Factor

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

VOC: Volatile Organic Compounds

DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)

EN: European Standard

ISO: International Organization for Standardization

IUCLID: International Uniform Chemical Information Database

LC50: Lethal Concentration, 50 %

LD50: Lethal Dose, 50 %

LL50: Lethal Loading, 50 %

OECD: Organisation for Economic Co-operation and Development

Safety Data Sheet

according to UK REACH Regulation

JMC Silikonentferner

Revision date: 11.09.2024

Page 14 of 14

EC50: Effective Concentration 50 %

M-Faktor: Multiplication Factor

EL50: Effect Loading, 50 %

ErC50: Effective Concentration 50 %, growth rate

M-Faktor: Multiplication Factor

NOEC: No Observed Effect Concentration

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

DGR: Dangerous Goods Regulations

EmS: Emergency Schedules

IATA: International Air Transport Association

IBC: Intermediate Bulk Container

ICAO: International Civil Aviation Organization

IE: Industrial Emissions

IMDG: International Maritime Code for Dangerous Goods

LQ: Limited Quantity

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

MFAG: Medical First Aid Guide

RID: Regulations concerning the International carriage of Dangerous goods by rail

TI: Technical Instructions

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)