

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **FUEL STABILIZER**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Gasoline additive

Only for proper handling.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MOTOREX AG

Bern–Zürich–Strasse 31, Postfach

CH–4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

Further information obtainable from: msds@motorex.com

1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
propan-2-ol

Hydrocarbons, C10, aromatics, >1% naphthalene

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 1)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains biocidal products: propan-2-ol

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	50-70%
EC number: 926-141-6 Reg.nr.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304, EUH066	25-50%
EC number: 919-284-0 Reg.nr.: 01-2119463588-24	Hydrocarbons, C10, aromatics, >1% naphthalene Carc. 2, H351; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	≥1-<2.5%
CAS: 91-20-3 EINECS: 202-049-5 Index number: 601-052-00-2 Reg.nr.: 01-2119561346-37	naphthalene Flam. Sol. 2, H228; Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥0.1-<0.25%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons

≥30%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
The recommended storage temperature is (deg.C): ≤50°C
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

· DNELs

67-63-0 propan-2-ol

Oral	DNEL/general population/Systemic effects/Long-term	26 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	888 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	319 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	500 mg/m ³ (worker)
	DNEL/general population/Systemic effects/Long-term	89 mg/m ³ (consumer)

91-20-3 naphthalene

Dermal	DNEL / Workers / Systemic effects / Long-term	3.57 mg/kg/24h (worker)
Inhalative	DNEL / Workers / Systemic effects / Long-term	25 mg/m ³ (worker)
	DNEL / Workers / Local Effects / Long-term	25 mg/m ³ (worker)

· PNECs

67-63-0 propan-2-ol

Oral	PNEC / Predators / Secondary poisoning	160 mg/kg food (secondary poisoning (predators))
	PNEC / Aquatic organisms / Freshwater	140.9 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Marine water	140.9 mg/l (aquatic organisms)
	PNEC / Aquatic org / intermittent releases(freshwater)	140.9 mg/l (aquatic organisms)
	PNEC/Aquatic organisms/Sewage treatment plant/STP	2,251 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (freshwater)	552 mg/kg (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (marine water)	552 mg/kg (aquatic organisms)
	PNEC / Terrestrial organism / Soil	28 mg/kg (terrestrial organisms)

91-20-3 naphthalene

	PNEC / Aquatic organisms / Freshwater	0.0024 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Marine water	0.0024 mg/l (Bioaccumulation)
	PNEC / Aquatic org / intermittent releases(freshwater)	0.02 mg/l (aquatic organisms)
	PNEC/Aquatic organisms/Sewage treatment plant/STP	2.9 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (freshwater)	0.0672 mg/kg (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (marine water)	0.0672 mg/kg (aquatic organisms)
	PNEC / Terrestrial organism / Soil	0.0533 mg/kg (terrestrial organisms)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 4)

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



safety goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Blue

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Undetermined.

· **Flammability**

Highly flammable.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

17 °C

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Consistency**

· **Dynamic:**

Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 5)

· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Heat Capacity	
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.805 g/cm ³ (ASTM D 4052)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent separation test:	
· VOC (EC)	86.70 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	16.4 ml/kg (rabbit)
	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50 / 6h	10,000 ppm (rat)
	NOAEC	5,000 ppm (rat)
	NOEC	500-5,000 ppm (rat)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	5,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	5.28 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m3 (rat)

91-20-3 naphthalene

Oral	LD50	533-710 mg/kg (mouse)
	NOEL	100 mg/kg/24h (rat)
	NOAEL	100-200 mg/kg/24h (mouse)
		200 mg/kg/24h (rat)
	LOAEL	400 mg/kg/24h (rat)
Dermal	LD50	2,500-16,000 mg/kg (rat)
	NOEL	300 mg/kg/24h (rat)
	NOAEL	1,000 mg/kg/24h (rat)
Inhalative	LC0 / 4h	77.7 ppm (rat)
	LC50 / 4h	77.7 ppm (rat)
	LC50 / 4h	400 mg/m3 (rat)
	NOAEL	300 mg/m3 (rat)
	NOAEC	1 ppm (rat)
	LOAEC	2-10 ppm (rat)
	LOAEC	11 mg/m3 (rat)
	NOEC	0.1 ppm (rat)

- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-63-0 propan-2-ol

LC50	9.64-10 mg/l/96h (fish)
LC50	10,000 mg/l/24h (aquatic invertebrates)
EC50	10,000 mg/l/24h (aquatic invertebrates)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

LL50	2-5 mg/l/96h (fish)
LL50	2-5 mg/l/48h (fish)
LL50	5-17 mg/l/24h (fish)
EL50	1.4 mg/l/48h (aquatic invertebrates)
EL50	4.6 mg/l/24h (aquatic invertebrates)
	1-3 mg/l/24h (algae / cyanobacteria)
EL50	1-3 mg/l/72h (algae / cyanobacteria)
EL50	0.81-0.89 mg/l/21d (aquatic invertebrates)
NOELR	1.22 mg/l/21d (aquatic invertebrates)
NOELR	1,000 mg/l/72h (algae / cyanobacteria)

91-20-3 naphthalene

LC50	1.6-7.9 mg/l/96h (fish)
LC50	6.35 mg/l/48h (fish)
LC50	6.08 mg/l/72h (fish)
LC50	2.4-7.76 mg/l/24h (fish)
EC50	0.4-0.5 mg/l/72h (algae / cyanobacteria)
EC50	2.16 mg/l/48h (aquatic invertebrates)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential

67-63-0 propan-2-ol

Partition coefficient	0.05 [---] (log Kow) (Bioaccumulation)
Biodegradability	>70 % (28d) (Biodegradability) (EU Method C.5)

91-20-3 naphthalene

Partition coefficient	3.4 [---] (log Kow) (Bioaccumulation)
Biodegradability	>74 % (28d) (Biodegradability) (OECD 301 C)

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 8)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1219

14.2 UN proper shipping name

ADR/RID/ADN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
IMDG, IATA ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3 Transport hazard class(es)

ADR/RID/ADN



Class 3 (F1) Flammable liquids.
Label 3

IMDG, IATA



Class 3 Flammable liquids.
Label 3

14.4 Packing group

ADR/RID/ADN, IMDG, IATA II

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code): 33

EMS Number: F-E,S-D

Stowage Category B

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 9)

· Transport/Additional information:**· ADR/RID/ADN****· Limited quantities (LQ)**

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

D/E

· IMDG**· Limited quantities (LQ)**

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P5c** FLAMMABLE LIQUIDS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· purity requirement**· Relevant phrases**

H225 Highly flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Abteilung Produktsicherheit**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Sol. 2: Flammable solids – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 * **Data compared to the previous version altered.**

Annex: Exposure scenario 1

- **Short title of the exposure scenario** Industrial use of additives
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC14 Metal surface treatment products
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
 PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
 PROC18 General greasing /lubrication at high kinetic energy conditions
 PROC20 Use of functional fluids in small devices
- **Environmental release category**
 ERC7 Use of functional fluid at industrial site
 ERC9a Widespread use of functional fluid (indoor)
 ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 11)

- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 2

- **Short title of the exposure scenario** Professional use of additives
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC14 Metal surface treatment products
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC18 General greasing /lubrication at high kinetic energy conditions
PROC20 Use of functional fluids in small devices
- **Environmental release category**
ERC9a Widespread use of functional fluid (indoor)
ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 3

- **Short title of the exposure scenario** Private use of additives
- **Sector of Use** SU21 Consumer uses: Private households / general public / consumers

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.01.2023

Version number 1.1 (replaces version 1.0)

Revision: 30.01.2023

Trade name: FUEL STABILIZER

(Contd. of page 12)

- **Product category** PC14 Metal surface treatment products
- **Process category**
 - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
 - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
 - PROC18 General greasing /lubrication at high kinetic energy conditions
 - PROC20 Use of functional fluids in small devices
- **Environmental release category**
 - ERC9a Widespread use of functional fluid (indoor)
 - ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
 - Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB