MOTOREX\*
Oil of Switzerland
Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SYSTEM GUARD
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Gasoline additive

Only for proper handling.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

**MOTOREX AG** 

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal Tel. +41 (0)62 919 75 75

www.motorex.com

- · Further information obtainable from: msds@motorex.com
- 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 (UK only).

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics propan-2-ol

Hydrocarbons, C10, aromatics, >1% naphthalene

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

(Contd. on page 2)

MOTOREX\*
Oil of Switzerland

Revision: 16.08.2024

Printing date 16.08.2024 Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains biocidal products: propan-2-ol

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25		≥50-≤70%
EC number: 926-141-6 Reg.nr.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304, EUH066	25-50%
EC number: 919-284-0 Reg.nr.: 01-2119463588-24	Hydrocarbons, C10, aromatics, >1% naphthalene Carc. 2, H351; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	≥1-<2.5%
CAS: 91-20-3 EINECS: 202-049-5 Index number: 601-052-00-2 Reg.nr.: 01-2119561346-37	naphthalene Flam. Sol. 2, H228; Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥0.1-<0.25%

## Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons ≥30%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

Immediately rinse with water.

(Contd. on page 3)

Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Storage class: 3

(Contd. on page 4)

MOTOREX\*
Oil of Switzerland

Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

8.1 Cont	rol parameters			
	nts with limit values that require monito	ring at the w	orkplace:	
67-63-0 p	propan-2-ol			
	ort-term value: 1250 mg/m³, 500 ppm			
	ng-term value: 999 mg/m³, 400 ppm			
DNELs				
	propan-2-ol			
Oral	DNEL/general population/Systemic effects/Long-term		,	
Dermal	DNEL / Workers / Systemic effects / Long-term		888 mg/kg/24h (worker)	
	DNEL/general population/Systemic effect	_	319 mg/kg/24h (consumer)	
Inhalative	,	_	500 mg/m3 (worker)	
01.00.0	DNEL/general population/Systemic effect	ts/Long-term	89 mg/m3 (consumer)	
	naphthalene		0.57 // /0.4/. /	
Dermal	DNEL / Workers / Systemic effects / Lon	•	3.57 mg/kg/24h (worker)	
Inhalative	DNEL / Workers / Systemic effects / Lon	_	25 mg/m3 (worker)	
	DNEL / Workers / Local Effects / Long-te	erm	25 mg/m3 (worker)	
PNECs				
	propan-2-ol			
Oral PN	al PNEC / Predators / Secondary poisoning		food (secondary poisoning	
PN	EC / Aquatic organisms / Freshwater	140.9 mg/l (a	aquatic organisms)	
	EC / Aquatic organisms / Marine water	140.9 mg/l (aquatic organisms)		
	EC/Aquatic org/intermittent ases(freshwater)	140.9 mg/l (á	aquatic organisms)	
PNEC/Aquatic organisms/Sewage treatment plant/STP		2,251 mg/l (a	aquatic organisms)	
PNEC / Aquatic organisms / Sediment (freshwater)		552 mg/kg (aquatic organisms)		
PNEC / Aquatic organisms / Sediment (marine water)		552 mg/kg (a	aquatic organisms)	
PN	EC / Terrestrial organism / Soil	28 mg/kg (terrestrial organisms)		
91-20-3 ı	naphthalene			
PN	EC / Aquatic organisms / Freshwater	0.0024 mg/l	(aquatic organisms)	
PN	EC / Aquatic organisms / Marine water	0.0024 mg/l	(Bioaccumulation)	
	EC/Aquatic org/intermittent ases(freshwater)	0.02 mg/l (ad	quatic organisms)	
	PNEC/Aquatic organisms/Sewage treatment plant/STP		uatic organisms)	
	PNEC / Aquatic organisms / Sediment (freshwater)		t 0.0672 mg/kg (aquatic organisms)	
	PNEC / Aquatic organisms / Sediment (marine water)		0.0672 mg/kg (aquatic organisms)	
1	EC / Terrestrial organism / Soil	0.0500	g (terrestrial organisms)	

Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

MOTOREX\*
Oil of Switzerland

Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 4)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



· Body protection: Protective work clothing

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid
Yellow
Alcohol-like
Not determined.
Undetermined.

Boiling point or initial boiling point and

boiling range 82 °C (DIN EN ISO 3405)
• Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 2 Vol %
 Upper: 12 Vol %
 Flash point: 16 °C

Auto-ignition temperature:
 Decomposition temperature:
 pH
 425 °C (DIN 51794)
 Not determined.
 Not determined.

· Viscosity:

• Kinematic viscosity
< 3 mm²/s @ 40 °C (DIN 51562-1)</p>

(Contd. on page 6)

Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 5)

· Consistency

· Dynamic:

· Solubility

· water:

· Partition coefficient n-octanol/water (log

value)

· Heat Capacity

· Vapour pressure at 20 °C:

Density and/or relative density

Density at 20 °C:

· Relative density · Vapour density

· 9.2 Other information

· Appearance:

· Form:

· Important information on protection of health

and environment, and on safety.

· Explosive properties:

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives · Flammable gases

· Aerosols · Oxidising gases

· Gases under pressure

Flammable liquids · Flammable solids

· Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids

· Self-heating substances and mixtures

· Substances and mixtures, which emit flammable gases in contact with water

· Oxidising liquids · Oxidising solids · Organic peroxides

· Corrosive to metals · Desensitised explosives

43 hPa

Fluid

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Not determined.

Not determined.

Not determined.

Not determined.

Not miscible or difficult to mix.

0.79 g/cm3 (ASTM D 4052)

Void Void

Void Void

Void Highly flammable liquid and vapour.

Void Void

Void Void Void

Void

Void Void Void

Void Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.



Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 6)

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	LD/LC50 values relevant for classification:		
67-63-0 pi	67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat)	
Dermal	LD50	16.4 ml/kg (rabbit)	
	LD50	12,800 mg/kg (rabbit)	
Inhalative	LC50 / 6h	10,000 ppm (rat)	
	NOAEC	5,000 ppm (rat)	
	NOEC	500-5,000 ppm (rat)	
	•	C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	
Oral	LD50	5,000 mg/kg (rat)	
	NOAEL	1,000-5,000 mg/kg/24h (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	5.28 mg/l (rat)	
	NOAEL	200 ppm (rat)	
	NOAEC	275-10,400 mg/m3 (rat)	
	aphthalene		
Oral	LD50	533-710 mg/kg (mouse)	
	NOEL	100 mg/kg/24h (rat)	
	NOAEL	100-200 mg/kg/24h (mouse)	
		200 mg/kg/24h (rat)	
	LOAEL	400 mg/kg/24h (rat)	
Dermal	LD50	2,500-16,000 mg/kg (rat)	
	NOEL	300 mg/kg/24h (rat)	
	NOAEL	1,000 mg/kg/24h (rat)	
Inhalative		77.7 ppm (rat)	
	LC50 / 4h	77.7 ppm (rat)	
	LC50 / 4h		
	NOAEL	300 mg/m3 (rat)	
	NOAEC	1 ppm (rat)	
	LOAEC	2-10 ppm (rat)	
	LOAEC	11 mg/m3 (rat)	
	NOEC	0.1 ppm (rat)	

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

— GI

MOTOREX Oil of Switzerland
Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 7)

### SECTION 12: Ecological information

#### · 12.1 Toxicity

· Aquatic	· Aquatic toxicity:			
67-63-0	propan-2-ol			
LC50	9.64-10 mg/l/96h (fish)			
LC50	10,000 mg/l/24h (aquatic invertebrates)			
EC50	10,000 mg/l/24h (aquatic invertebrates)			
Hydroca	arbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
LL50	2-5 mg/l/96h (fish)			
LL50	2-5 mg/l/48h (fish)			
LL50	5-17 mg/l/24h (fish)			
EL50	1.4 mg/l/48h (aquatic invertebrates)			
EL50	4.6 mg/l/24h (aquatic invertebrates)			
	1-3 mg/l/24h (algae / cyanobacteria)			
EL50	1-3 mg/l/72h (algae / cyanobacteria)			
EL50	0.81-0.89 mg/l/21d (aquatic invertebrates)			
NOELR	1.22 mg/l/21d (aquatic invertebrates)			
NOELR	1,000 mg/l/72h (algae / cyanobacteria)			
91-20-3	naphthalene			
LC50	1.6-7.9 mg/l/96h (fish)			
LC50	6.35 mg/l/48h (fish)			
LC50	6.08 mg/l/72h (fish)			
LC50	2.4-7.76 mg/l/24h (fish)			
EC50	0.4-0.5 mg/l/72h (algae / cyanobacteria)			
EC50	2.16 mg/l/48h (aquatic invertebrates)			

#### 12.2 Persistence and degradability No further relevant information available.

#### · 12.3 Bioaccumulative potential

#### 67-63-0 propan-2-ol

Partition coefficient 0.05 [---] (log Kow) (Bioaccumulation)

Biodegradability >70 % (28d) (Biodegradability) (EU Method C.5)

#### 91-20-3 naphthalene

Partition coefficient 3.4 [---] (log Kow) (Bioaccumulation)

Biodegradability | >74 % (28d) (Biodegradability) (OECD 301 C)

- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

GB

MOTOREX\*
Oil of Switzerland
Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 8)

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information	n
14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1219
14.2 UN proper shipping name ADR/RID/ADN IMDG, IATA	1219 ISOPROPANOL (ISOPROPYL ALCOHOL ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3 Transport hazard class(es)	
ADR/RID/ADN	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR/RID/ADN, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler cod	Warning: Flammable liquids.
EMS Number: Stowage Category	F-E,S-D B
14.7 Maritime transport in bulk according IMO instruments	to Not applicable.

(Contd. on page 10)

MOTOREX\*
Oil of Switzerland

Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

	(Contd. of page
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
· Transport category · Tunnel restriction code	2 D/E
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
· UN "Model Regulation":	UN 1219 ISOPROPANOL (ISOPROPY) ALCOHOL), 3, II

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- Relevant phrases

H225 Highly flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

(Contd. on page 11)

Revision: 16.08.2024

Printing date 16.08.2024 Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 10)

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Department issuing SDS: Abteilung Produktsicherheit

#### Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Sol. 2: Flammable solids – Category 2 Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

· \* Data compared to the previous version altered.

### Annex: Exposure scenario 1

- · Short title of the exposure scenario Industrial use of additives
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC14 Metal surface treatment products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC18 General greasing /lubrication at high kinetic energy conditions

PROC20 Use of functional fluids in small devices

#### Environmental release category

ERC7 Use of functional fluid at industrial site

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.

(Contd. on page 12)

Printing date 16.08.2024 Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

Revision: 16.08.2024

(Contd. of page 11)

- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

## Annex: Exposure scenario 2

- · Short title of the exposure scenario Professional use of additives
- Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC14 Metal surface treatment products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC18 General greasing /lubrication at high kinetic energy conditions

PROC20 Use of functional fluids in small devices

Environmental release category

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- · Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

### Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of additives
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers

(Contd. on page 13)

Revision: 16.08.2024

Printing date 16.08.2024

Version number 4.2 (replaces version 4.1)

Trade name: SYSTEM GUARD

(Contd. of page 12)

- · Product category PC14 Metal surface treatment products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC18 General greasing /lubrication at high kinetic energy conditions

PROC20 Use of functional fluids in small devices

· Environmental release category

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.